

Dimensions shown may be changed without prior notice

// 720AA

**EVOLUTION****Bulk material S&D 10 bar (150 psi)****Tube:** black conductive NR - abrasion resistant.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** black conductive SBR/NR - abrasion and ozone resistant.**Application:** bulk material suction and delivery in heavy duty applications. Specially designed for dry cement, grain and animal feed transfer.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"	65,00	2,56	10	150	30	450	102	4,02	100	1,430	0,97
63,0	2 1/2"	77,00	3,03	10	150	30	450	189	7,44	90	1,900	1,28
76,0	3"	90,00	3,54	10	150	30	450	228	8,98	90	2,280	1,54
76,0	3"	92,00	3,62	10	150	30	450	228	8,98	90	2,600	1,75
102,0	4"	116,00	4,57	10	150	30	450	306	12,05	90	3,180	2,14
102,0	4"	118,00	4,65	10	150	30	450	306	12,05	90	3,600	2,42
127,0	5"	143,00	5,63	5	75	15	225	508	20,00	80	4,750	3,20
127,0	5"	145,00	5,71	5	75	15	225	508	20,00	80	5,270	3,55
152,0	6"	168,00	6,61	5	75	15	225	608	23,94	80	5,950	4,00

// 7P1AA **NEW****EVOLUTION PLUS****Bulk material S&D - Square corrugated - Extra flexible****Tube:** black conductive NR - abrasion resistant.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** black conductive SBR/NR - abrasion and ozone resistant.**Application:** bulk material suction and delivery. Special construction for maximum flexibility.**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)

↔		↔		↻		↻		⤴		⚖		
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
51,0	2"	67,00	2,64	10	150	30	450	51	2,01	100	1,630	1,10
63,0	2 1/2"	79,00	3,11	10	150	30	450	126	4,96	90	2,240	1,51
76,0	3"	92,00	3,62	10	150	30	450	152	5,98	90	2,650	1,78
102,0	4"	120,00	4,72	10	150	30	450	204	8,03	90	3,720	2,50
127,0	5"	145,00	5,71	5	75	15	225	381	15,00	80	5,400	3,63
152,0	6"	170,00	6,69	5	75	15	225	456	17,95	80	6,720	4,52