

▣ HR-30S-Ex [SUS316] - ORDER CODE



BASIC SPECIFICATIONS

Installation : Band

Ambient Temp. : -20 ~ +60°C

S/W Type : Reed

Enclosure : Ex-Proof(Ex d IIC T6,IP65)

Sensor Material : 316

Combination Gauge : HLG-100F(Max.150°C)

Length : Std. 1000mm

SELECTION OF PROPERTY-KIND

Housing ; Cable Entry

- **AB** : AL. ; PF 3/4"(F), IP65

Contact Form

- **AG : 2-SPST**
- AH : 3-SPST
- AI : 4-SPST

Length

- **AD : ~1,000mm**
- AE : ~1,500mm
- AF : ~2,000mm
- AG : ~2,500mm
- AH : ~3,000mm
- AI : ~3,500mm
- AJ : ~4,000mm
- AK : ~4,500mm
- AL : ~5,000mm

Approval

- **AA : Ex-Proof (KOSHA)**

Cable Entry(Adapter) Option

- AG : PF 1/2"(F), Ex d IIC
- AH : NPT 1/2"(F), Ex d IIC
- **AI : NPT 3/4"(F), Ex d IIC**
- AJ : PT 1/2"(F), Ex d IIC
- AK : PT 3/4"(F), Ex d IIC
- AM : M20 x1.5, Ex d IIC

Call HITROL

- **AF : Special(Customize)**

HR-30S-Ex SUS316 - [AB] [AG] [AD] [AA] [AI] [AF]